Ricoh Aficio MP 6000/MP 7000/MP 8000 Digital Imaging System Perform at Peak Productivity.




Alicio









Efficiency Expert

True productivity requires much more than raw speed. It also demands high uptime, long-term reliability, easy operation and flexible capabilities. Whether you need to add capacity to a production-grade fleet or accelerate workflow in large, fast-paced workgroups, the RICOH® Aficio® MP 6000/MP 7000/MP 8000 digital imaging systems have what it takes to produce high-quality black & white documents with outstanding efficiency.



SpeedInnovationWorkflowFinishing

Intuitive, Easy Operation

With its simple, user-friendly design and versatile capabilities, the Ricoh Aficio MP 6000/MP 7000/ MP 8000 can easily handle a wide range of important tasks.

- Make quick work of the largest jobs with output speeds of 60, 70 or 80 pages-per-minute and a single-pass document feeder that scans up to 75 originals-per-minute.
- Expect superior image quality with true 1200 x 1200 dpi resolution.
- Complete every job with one multifunctional product (MFP) that offers high-end digital copying, plus optional printing, scanning, faxing and finishing.
- Program jobs without delay using the large, easy-to-read WVGA touch-screen operation panel.
- Immediately authenticate for full system access or log out in seconds with the login/logout shortcut button.
- Eliminate repetitive programming for frequent jobs. Create one-step icons that automatically apply correct settings and procedures.

Efficient Document Handling

This fully featured MFP offers the tools necessary to save time and distribute documents effectively.

- Reduce errors with Sample Print by checking a proof before running the remaining sets. Or confirm document content prior to printing from the Document Server with File Preview.
- Ensure confidentiality with Locked Print, which releases files for output only after users enter the correct password at the system.
- Improve convenience with Stored Print, which saves frequently printed documents and finishing settings in memory for instant output.
- Reduce network traffic with Scan-to-URL, which allows you to send URL links to documents stored on the MFP's hard drive instead of e-mailing large attachments.
- Find e-mail addresses for Scan-to-Email recipients faster. Search your corporate database via the standard Lightweight Directory Access Protocol (LDAP).

Maximum Security

Protect sensitive data during every phase of workflow, including copying, printing, scanning and distribution.

- Safeguard confidential information with Unauthorized Copy Control. It embeds a masking pattern in originals that obscures documents if they are copied on other systems with this capability.
- Safeguard sensitive PDFs by assigning passwords for access. Without the right password, unintended recipients will not be able to open the encrypted file.
- Eliminate "from field" e-mail spoofing by restricting access to the Document Server.
- Remove the risk of a stolen hard drive with the DataOverwriteSecurity System (DOSS), which erases latent image data from memory after every job. Or select the optional Removable Hard Drive, which can be stored in a secure location.
- Prevent unauthorized access with up to 500 unique user authentication codes.



Rely on the Ricoh Aficio MP 6000/MP 7000/ MP 8000 to create a variety of attractive, professionally finished documents.



The highly reliable, single-pass document feeder is capable of scanning up to 75-images-per-minute.



Use the GBC StreamPunch III to produce clean, precisely punched documents in a range of styles.

CopyScanPrintFax

Superior Finishing

Produce fantastic-looking output and keep more jobs in-house with the Ricoh Aficio MP 6000/MP 7000/MP 8000 system's full lineup of professional finishing options.

- Make saddle-stitched booklets quickly and costeffectively using the BK5010 Production Booklet Maker.
- Liven up black & white documents by adding pre-printed, full-color covers with the interposer.
- Keep reports, analyses and other long documents clean and well-ordered with the 100-Sheet stapling finisher.
- Accommodate over-sized pages such as engineering drawings within conventional documents with the Z-fold unit.
- Create expertly punched, ready-to-bind documents with the GBC StreamPunch III.

Comprehensive Faxing

The Ricoh Aficio MP 6000/MP 7000/ MP 8000 includes a powerful set of fax capabilities.

- Maximize fax productivity with up to three analog lines, all of which can send or receive faxes simultaneously.
- Send fax documents with 2 seconds-per-page transmission speed using the Super G3 modem and standard JBIG compression.
- Save time and paper with LAN Faxing. Send a document to a fax number right from the desktop, instead of printing and scanning it.
- Reduce transmission costs with IP Faxing (T.38). This fast, high-quality method lets users send and receive faxes over the LAN or WAN, with virtually instant confirmation of receipt.
- Automatically forward incoming faxes to e-mail addresses or network folders, instead of letting them sit unattended in the output tray. Recipients receive an automatic e-mail notification of all fax deliveries.

Advanced Functionality

Improve workflow even more with innovative document management tools.

- Customize the MFP's operation panel, printing, file saving, scanning or other functions so the system is completely aligned with your business needs using the Java-compatible (J2ME) software development platform.
- Focus on core tasks without spending time collecting and reporting the MFP's usage. The optional @Remote Intelligent Remote Management System reports meter usage data automatically and securely.
- Enable users to securely store, edit, share and retrieve documents and files from PCs via the Internet with DocumentMall. This solution also allows you to scan documents into a secure DocumentMall folder directly from the MFP.



Your Environmental Partner



Ricoh continues its long-standing commitment to developing office solutions with environmentally friendly and superior energy- and supplysaving features, without compromising productivity, including:

- Quick Start-Up (QSU) Technology
- Power-Saving Sleep Modes
- Duplex and Combine Copy Modes
- Toner Recycling
- Low Noise Levels
- Minimal Ozone Emissions
- Restriction of Hazardous Substances (RoHS) Compliant

VersatileProductiveReliableEfficient

Ensure Fast, Professional Results.



Fax Forwarding



Prevent incoming fax documents from sitting unattended. Use the Fax Forwarding feature to deliver these files to a secure network folder or e-mail address.

Ricoh Aficio MP 6000/MP 7000/MP 8000 Specifications



Specifications Memory (RAM) Basic Models: 256 MB std/512 MB max S/P Models: 512 MB std/max HDD 80 GB First Copy Time MP 6000: 4.2 seconds MP 7000/MP 8000: 3.5 seconds Warm-Up Time MP 6000/MP 7000: 30 seconds from power off MP 8000: 60 seconds from power off 60/70/80 copies/minute multiple sets Copy Speed (Letter LEF) Up to 11" x 17" (12" x 18" using platen) 5.5" x 8.5" - 11" x 17" True 1200 x 1200 dpi Original Size Copy Size Copy Resolution Grayscale 256 levels Zoom 25% - 400% in 1% increments Standard: Tray 1: 1,550 sheets x 2 (tandem) = 3,100 (Letter); Trays 2 & 3: 550 sheets each (user Paper Capacity adjustable) Bypass: 100 sheets Total Standard/Max: 4,300/8,300 sheets Paper Weight Trays 1 - 3: 14 lb. - 34 lb. Bond; Bypass (Thick Paper Mode): 14 lb. Bond - 110 lb. Index (216 g/m²) 120V/60Hz/20A (Requires dedicated Power Source 20A outlet) 27.2" x 31.1" x 45.9" Dimensions (WxDxH) 454 lbs. Weight System Accessories Automatic Document Feeder (Standard) 5.5" x 8.5" - 11" x 17" Simplex: 11 lb. - 34 lb. Bond Duplex: 14 lb. - 34 lb. Bond Original Size Paper Weight Capacity 100 sheets Options RT43 Large-Capacity Tray (LCT) Paper Size 8.5" x 11" LEF Paper Weight 14 - 34 lb. Bond Paper Capacity Dimensions (WxDxH) 4,000 sheets (20 lb. Bond) 12.4" x 18.0" x 25.9" 8.5" x 14" Paper Size Tray Type 1075 Enables legal-size (8.5" x 14") paper to be fed through LCT. Paper Size 8.5" x 14", 8.5" x 11" SEF Paper Capacity 2,500 sheets (20 lb. Bond) Paper Size Paper Capacity CS391 9-Bin Mailbox Compatible with SR970 and SR4000 Finishers Number of Bins Stack Capacity 9 100 sheets/bin (20 lb. Bond) Paper Size 5.5" x 8.5" - 11" x 17 Copy Tray Type 2075 500 sheets (8.5" x 11"), 250 sheets (8.5" x 14", 11" x 17") Paper Capacity 11" x 17" Tray Type 1075 Enables 11" x 17" and 8.5" x 14" paper to be fed from Tray 1. Paper Size 11" x 17" SEF, 8.5" x 14" SEF, 8.5" x 11" Paper Size Paper Capacity 1,000 sheets Cover Interposer Tray Type 3260 Compatible with all three finishers. Paper Size 5.5" x 8.5" - 11" x 17" Paper Weight 17 lb. Bond - 110 lb. Index (216 g/m²) Paper Capacity 200 sheets (20 lb. Bond) Z-Folding Unit Type ZF4000 Compatible only with SR842 and SR4000 Finishers. Right, left, bottom 8.5" x 11" SEF, 8.5" x 14" SEF, 11" x 17" SEF Z-Folding Positions Paper Size Paper Weight 17 lb. - 20 lb. Bond SR4000 2,000-Sheet Finisher with Saddle Stitch Proof Tray 5.5" x 8.5" - 11" x 17" SEF, 12" x 18" SEF Paper Size 12 * X18 * SEF 14 lb. Bond - 90 lb. Index (163 g/m²) 250 sheets (8.5" x 11" or smaller), 50 sheets (8.5" x 14" or larger) 30 sheets (Z-fold/8.5" x 14" or larger) 20 sheets (Z-fold/8.5" x 11" or smaller) Paper Weight Stack Capacity

Shift Tray 5.5" x 8.5" - 11" x 17" SEF, Paper Size 12" x 18" SEF 12" x 18" SEF 14 lb. Bond - 110 lb. Index (216 g/m²) 2,000 sheets (8.5" x 11" LEF) 1,000 sheets (8.5" x 11" SEF, 8.5" x 14" SEF, 11" x 17" SEF, 12" x 18" SEF) 100 sheets (5.5" x 8.5" SEF) 30 sheets (Z-fold/8.5" x 14" or larger) 20 sheets (Z-fold/8.5" x 11" or smaller) Paper Weight Stack Capacity **Staple Capacity** 50 sheets (8.5" x 11" or smaller) 30 sheets (8.5" x 14" or larger) 30 sheets (8.5" x 11", 11" x 17") Same Paper Size Mixed Paper Size Z-Fold Paper Only Saddle Stitch 5 sheets 15 sheets (8.5" x 11" SEF, 8.5" x 14" SEF, 11" x 17" SEF) Top, bottom, 2 staples, top slant 25.9" x 24.1" x 37.8" Staple Position Dimensions (WxDxH) Punch Unit Type 3260 2 or 3 holes 5.5" x 8.5" - 11" x 17" Hole Positions Paper Size 14 lb. Bond - 90 lb. Index (163 g/m²) Paper Weight SR842 3,000-Sheet Finisher w/100-Sheet Stapler **Proof Tray** 5.5" x 8.5" - 11" x 17" SEF, Paper Size 12" x 18" SEF 12 x 16 SEF 14 lb. Bond - 110 lb. Index (216 g/m²) 500 sheets (8.5" x 11" or smaller), 250 sheets (8.5" x 14" or larger) Paper Weight Stack Capacity 30 sheets (Z-fold) Shift Tray 5.5" x 8.5" - 11" x 17" SEF, 12" x 18" SEF Paper Size 14 lb. Bond - 110 lb. Index (216 g/m²) Paper Weight 3,000 sheets (8.5" x 11" LEF) 1,500 sheets (8.5" x 11" SEF, 8.5" x 14" SEF, 11" x 17" SEF) 500 sheets (5.5" x 8.5" LEF) 100 sheets (5.5" x 8.5" SEF) Stack Capacity 30 sheets (Z-fold) **Staple Capacity** 100 sheets (8.5" x 11") 50 sheets (8.5" x 14", 11" x 17") 50 sheets (8.5" x 11" LEF, 11" x 17" SEF) Same Paper Size Mixed Paper Size Z-Fold Paper Only Staple Positions 10 sheets Top, top slant, bottom, 2 staples Dimensions (WxDxH) 31.5" x 28.7" x 38.6" Punch Unit Type 1075 Hole Positions 2 or 3 holes Paper Size 5.5" x 8.5" - 11" x 17" Paper Weight 14 lb. - 34 lb. Bond GBC StreamPunch III Paper Size 8.5" x 11" LEF Paper Weight 20 lb. Bond - 110 lb. Index (216 g/m²) CombBind®, Twin Loop Wire (2:1 or 3:1), ColorCoil®, VeloBind®, Three-Ring, Die Sets ProClick[®] **BK5010 Production Booklet Maker** 8 5" x 11" - 11" x 17" Paper Size Paper Weight 16 lb. Bond - 110 lb. Index (216 g/m²) SR970 3,000-Sheet Finisher w/50-Sheet Stapler Proof Tray 5.5" x 8.5" - 11" x 17" SEE 12" x 18" SEE Paper Size Paper Weight 14 lb. Bond - 90 lb. Index (163 g/m2) 250 sheets (8.5" x 11" or smaller), 50 sheets (8.5" x 14" or larger) Stack Capacity Shift Tray 5.5" x 8.5" - 11" x 17" SEF, 12" x 18" SEF Paper Size Paper Weight 14 lb. Bond - 110 lb. Index (216 g/m²) 3,000 sheets (8.5" x 11" LEF); 1,500 sheets (8.5" x 11" SEF, Stack Capacity 8.5" x 14" SEF, 11" x 17" SEF, 12" x 18" SEF) 100 sheets (5.5" x 8.5" SEF) Staple Capacity 50 sheets (8.5" x 11" or smaller) 30 sheets (8.5" x 14" or larger) 30 sheets (8.5" x 11" LEF, 11" x 17" SEF) Same Paper Size

Mixed Paper Size Staple Positions Dimensions (WxDxH)

Modem Speed Compression Method G3 Transmission Speed Scan Speed Auto Dialing SAF Memory Capacity Additional Modes Options Top, bottom, 2 staples, top slant 25 9" x 24 1" x 37 8'

MP 6000: 60 prints/minute MP 7000: 70 prints/minute MP 8000: 80 prints/minute Intel Celeron LV 866 MHz Standard: 10Base-T Ethernet/ 100Base-TX Ethernet, USB 2.0 Host Interface Optional: IEEE 1284 (Parallel), IEEE 802.11b (Wireless LAN), IEEE 1394, Bluetooth, 1000Base-T Ethernet Network Protocol TCP/IP, IPX/SPX, SMB, AppleTalk 512 MB DDR-SDRAM Memory Capacity Standard: RPCS, PCL5e, PCL6 Optional: Adobe PostScript 3 PCL5e: 300/600 dpi Print Resolution PCL6: 600/1200 dpi PS 3: 600/1200 dpi RPCS: 300/600/1200 dpi PCL5e/PCL6: Windows 2000/XP/ Server 2003/Vista RPCS: Windows 2000/XP/Server 2003/ Vista PS 3: Windows 2000/XP/Server 2003/ Vista, Macintosh OS 8.6 and later,

2 or 3 holes 5.5" x 8.5" - 11" x 17"

14 lb. Bond - 90 lb. Index (163 g/m2)

Punch Unit Type 3260

Print Controller Specifications

Hole Positions

Paper Weight

Print Speed

CPU

PDL

Drivers

Paper Size

Mac OS X Classic, Mac OS X Native v. 10.1 and later **Scanner Specifications**

75 sides/minute (200 dpi) Scan Speed 100 dpi - 600 dpi (100 -1200 dpi with TWAIN) **Optical Resolution Output Format** TIFF (Multi/Single), JPEG, PDF (Multi/Single) Standard: 10Base-T Ethernet/ Interface Support 100Base-TX Ethernet; Optional: IEEE 802.11b, IEEE 1394, 1000Base-T Ethernet **Bundled Drivers** Network TWAIN Yes (up to 500 addresses per send) Scan-to-Email LDAP Support Yes (Version 3) Max Stored 2,000 Destinations Authentication SMTP/POP before SMTP Yes (up to 50 folders per job) SMB, FTP, NCP Scan-to-Folder Protocol Support **Facsimile Specifications (Optional)** ITU-T (CCIT) G3, Additional G3 Type (Optional) Circuit PSTN, PBX 200 x 100 dpi (Standard Mode); 200 x 200 dpi (Detail Mode); 400 x 400 dpi Resolution (Super Fine Mode; available with optional SAF memory) 33.6 Kbps with auto fallback MH, MR, MMR, JBIG Approximately 2 seconds/page (with JBIG); Approximately 3 seconds/page (with MMR) 0.50 seconds/page (Standard/Detail/ Super Fine Mode; LTR SEF) 2,000 Quick Dials, 100 Group Dials (500 locations each) Standard: 4 MB (Approximately 320 pages); Maximum: 28 MB (approximately 2,240 pages) with memory option Internet Fax by e-mail (T.37), IP Fax (T.38), LAN Fax, Fax Forward to E-mail/ Folder, LDAP support G3 Interface Unit Type 7500 (provides one additional G3 line; up to two lines

For maximum performance and yield, we recommend using genuine Ricoh parts and supplies.

Wi Fi

may be added for a maximum of three

lines); 32 MB Memory 400 dpi/SAF

RICOH www.ricoh-usa.com

Ricoh Corporation, Five Dedrick Place, West Caldwell, NJ 07006 Ricoh* and the Ricoh Logo are registered trademarks of Ricoh Company, Ltd. Windows* 95/98/Me/NT4 0/2000/XP/Vista are registered trademarks of Microsoft Corporation. Macintosh*, Mac* OS and Applicalit* are registered trademarks of Apple Computer, Inc. Adobe* and PostScript* are registered trademarks of Adobe Systems, Inc. PCL* is a registered trademark of Hewlett-Packard Company, RPCS* a trademark of Ricoh Company, Ltd. All other trademarks are the property of their respective owners. Printed in U.S.A. on recycled paper. Print speed may be affected by network, application on PC performance Specifications and external appearances are subject to change without notice. Products are shown with optional Teatures. R2744 R2744